



שרוולי וידופלקס

32 25 19 13 9 6 4							<<<< עובי דופן							תחום קוטר פנימי (מ"מ)	קוטר פנימי נומינלי
מטרים בקרטון							מתאים לצינור בעל קוטר חיצוני					נחושת			
							פלסטיק	פלדה		אינצ'					
							מ"מ	מ"מ	אינצ'	מ"מ	אינצ'				
-	-	-	192	312	528	-	-	-	-	6.35	1/4"	6.5-8.5	6		
-	-	-	-	-	456	-	-	-	-	7.9	5/16"	8.5-10.5	8		
-	-	96	192	264	384	-	-	10.3	1/8"	9.5	3/8"	10.5-12.5	10		
-	-	88	144	216	312	-	12	-	-	12.7	1/2"	13-14.5	12		
-	-	72	120	184	240	-	16	-	-	15.9	5/8"	16.5-18	15		
30	48	66	120	144	216	-	-	-	-	19.05	3/4"	19.5-21	18		
30	42	60	96	120	168	220	20	21.3	1/2"	22.2	7/8"	22.5-24.5	22		
-	-	60	84	104	144	-	25	-	-	25.4	1"	26-28	25		
-	36	48	72	96	144	160	-	26.7	3/4"	27	1 1/16"	28-30	27		
24	36	48	72	96	144	-	-	-	-	28.6	1 1/8"	29-31	28		
18	28	40	72	72	96	-	32	33.4	1"	34.9	1 3/8"	36-39	35		
18	28	30	48	66	84	-	40	42.2	1 1/4"	41.3	1 5/8"	43-46	42		
16	20	28	42	60	-	-	-	48.3	1 1/2"	-	-	50-53	48		
14	20	24	42	48	-	-	50	-	-	54	2 1/8"	55-58	54		
14	20	24	42	48	-	-	-	-	-	57.1	2 1/4"	55-58	57		
12	18	24	36	48	-	-	-	60.3	2"	60.3	2 8/3"	62-65.5	60		
12	14	22	36	46	-	-	63	-	-	66.7	2 5/8"	67-70.5	67		
-	12	18	28	42	-	-	-	-	-	69.85	2 3/4"	72-76	70		
10	12	16	28	42	-	-	75	73	2 1/2"	76.2	3"	78-82	76		
-	12	16	28	-	-	-	-	-	-	79.4	3 1/8"	82-86	80		
8	12	16	24	36	-	-	90	88.9	3"	88.9	3 1/2"	91.5-96	90		
6	10	12	20	-	-	-	-	-	-	104.8	4 1/8"	106-111	104		
-	10	12	20	32	-	-	110	-	-	108	4 1/4"	110-116	108		
6	10	12	18	30	-	-	-	114.3	4"	114.3	4 1/2"	117-123	114		
6	-	10	-	-	-	-	140	141.3	5"	140	-	141.5-145.5	140		

*שרוולי הבידוד נחתכים לאורך סטנדרטי של 2 מטר (±1.5%)
ונאזרים בארגזי קרטון במידות : 210x38x33 ס"מ.